

PNEUMATIC ROD GRINDER



Rod grinder developed especially for the toughest applications (e.g. deburring work) with high power reserves.

DSG 22 Power
Straight Model
1. Art. No. 0703 234 0

DSG 25
Straight Model
2. Art. No. 0703 230 0

Long-life, handy rod grinders with tool-free speed control and rubber-coated handle against vibrations and cold hands.

DSW 22
Angled Design
3. Art. No. 0703 231 0

Delivery Scope			
Designation	Delivery scope	Art. No.	P. Qty.
Pneumatic Rod Grinder DSG 22 Power	1	0703 234 X	1
Combination Open-Ended Wrench, 14/19	1	0709 234 027	1
Combination Open-Ended Wrench, 14/19	1	0709 234 028	1

Delivery Scope			
Designation	Delivery scope	Art. No.	P. Qty.
Pneumatic Rod Grinder DSG 25/DSW 22	1	0703 230X / 0703 231 X	1
Combination Open-Ended Wrench, 11/17 mm	1	0709 230 027	2

Technical Data									
Model	Chuck dia. in mm	Speed in rpm	Weight in kg	Dimensions (l x w x h)	Avg. air cons in l/min.	Output in W	Connection thread	Min hose dia. in mm	Art. No.
DSG 22 Power	6	22,000	0.7	180 x 45 x 65	113	373	R 1/4"	8	0703 234 0
DSG 25	6	25,000	0.4	158 x 38 x 60	113	224	R 1/4"	8	0703 230 0
DSW 22	6	22,000	0.5	158 x 38 x 75	113	224	R 1/4"	8	0703 231 0

Additional Products



Mini/Flexi-Disk Assortment, 12-piece
Art. No. 0578 01

Mini Fiber Disks
Art. No. 0580 005 .../
0580 007 ...

Mini Fleece Disks
Art. No. 0673 205 .../
0673 207 ...

Mini Compact Fleece
Art. No. 0673 215 040 /
0673 217 540

Mini Nylon Fleece Disks
Art. No. 0673 22 50
Art. No. 0673 22 75

Bristle Disk
Art. No. 0673 000 50
Art. No. 0673 000 75

Art. No. 0586 578 01
Art. No. 0586 578 02

Carbide Milling Tips
Art. Pre-No. 0616

Mini Cutoff and Roughing Wheels
Art. No. 0664 100 ..
Art. No. 0664 130 ..
Art. No. 0664 160 606

Clamping Mandrels
Art. No. 0664 976
Art. No. 0664 978

Rubber-coated handle.
For warm hands.

Light, compact design.
Fatigue-free, low vibration operation.

Swiveling compressed-air connection.
No twisting of connection hose.

Warranty
2 Years Warranty on manufacturing and material defects. Excluded are damages caused by improper use, overloading or failure to observe the operating instructions. The current WÜRTH MASTER warranty conditions must be observed.

Available in the fleet management system ORSY®fleet.

Accessories		
Designation	Art. No.	P. Qty.
Plug-in nipple with R 1/4" male thread, made of nickel-plated steel	0699 100 614	
Small mist oiler	0699 070 314	1
Special oil for pneumatic tools (1 l)	0893 050 5	1

When used regularly, the machine should be lightly oiled via the compressed-air supply every day. The use of a mist oiler is recommended.