

PNEUMATIC NAIL GUN



Especially lightweight and handy nail gun for nails with a diameter of 1.2 mm, and a length of 15-54 mm. The machine is used on door moldings, wall elements, profile moldings, bandings, ornaments, decorative profiles, decorative moldings, door panels and baseboards.

DSK 1555
Art. No. 0703 547 0

- Powerful, oil-free drive therefore maintenance-free.
- Empty magazine recognition.
- Toolless depth adjustment for protecting work surfaces.
- Dual-function switch for changing from single triggering to contact triggering.
- Toolless access for easy troubleshooting.
- Adjustable air ejection.
- Belt hook.
- Rubber nose piece for use on sensitive surfaces.
- Supplied in a case.

Warranty

2 Years Warranty on manufacturing and material defects. Excluded are damages caused by improper use, overloading or failure to observe the operating instructions. The current WÜRTH MASTER warranty conditions must be observed.

Delivery scope		
Designation	Art. No.	P. Qty.
DSK 1555 Pneumatic Nail Gun	0703 547 0	1
Empty Carrying Case	0955 703 547	1
Safety Goggles	-	1
Offset Screwdrivers	-	1
Allen head 3 and 4 mm	-	1
Operating Instructions	-	1

Technical data	
Nail dia.	1.2 mm
Nail length	15-54 mm
Magazine capacity	105 nails
Working pressure	4.8-8.3 bar
Max. operating pressure	8.3 bar
Air consumption	approx. 1.13 l / impact
Minimum hose dia.	6 mm
Compressed-air supply	1/4"
Weight	1.09 kg
Dimensions (L x W x H)	241 x 67 x 245 mm

Suitable accessories

Version	Art. No.	P. Qty.
Plug-in nipple (brass) 1/4"	0699 211 4	1
Plug-in nipple (steel) 1/4"	0699 211 41	1
Quick-action coupling (brass) 6 mm	0699 126	1
Quick-action coupling (steel) 6 mm	0699 126 1	3
Quick-action coupling (safety) 6 mm	0699 152 6	1
Small mist oiler 1/4"	0699 070 314	1
Compressed air service oil, 1 liter	0893 050 5	1
Compressed air hose, inside dia. 6 mm	0699 906 1	10 m

Suitable compressed-head nails, Type WX and WY

- Version: Galvanized steel, blue passivated (A2K).

Version	Dia. in mm	Length in mm	Art. No.	P. Qty.
Galvanized steel, Type WX	1.2	16	0480 12 16	5000
	1.2	19	0480 12 19	5000
	1.2	25	0480 12 25	5000
	1.2	30	0480 12 30	5000
	1.2	35	0480 12 35	5000
	1.2	38	0480 12 38	5000
	1.2	40	0480 12 40	5000
	1.2	45	0480 12 45	5000
	1.2	50	0480 12 50	5000
	1.2	54	0480 12 54	5000
dark brown, Type WX, galv.	-	35	0480 12 351	5000
white, Type WX, galv.	-	35	0480 12 353	5000
light brown, Type WX, galv.	-	35	0480 12 354	5000
small head, type WX, galv.	1.0	16	0480 13 16	5000
	1.0	19	0480 13 19	5000
	1.0	25	0480 13 25	5000
	1.0	32	0480 13 32	5000
	1.0	38	0480 13 38	5000

These versions can also be used in machines of the competition (see comparison list).

Suitable compressor K 290

Art. No. 0701 229

Consumption example:

40 nails/min. x 1.13 l/nail gives an air consumption of 45 l/min. The K 290 compressor supplies 152 l/min., which means that there is sufficient reserve. Adjust operating pressure on pressure reducer!

