

PNEUMATIC IMPACT WRENCH



Extremely rugged and powerful impact wrench with quick torque buildup.

Ideal for tough applications, e.g. service work on trucks and buses, construction and agricultural equipment and industrial maintenance and repair work.

DSS 1" P
Art. No. 0703 775 0

Technical data												
Type	Square drive	Working torque* in Nm	Max. loosening torque in Nm	Avg. operating pressure in bar	Weight in kg	Dimensions (L x W x H) in mm	Avg. air consumption in L/min.	Connection thread in inches	Minimum hose dia. in mm	Sound pressure level in dB(A)	Art. No.	P. Qty.
DSS 1" P	1"	895 - 1,694	2,440	6.3	9.97	305 x 104 x 276	310	1/2"	11	93	0703 775 0	1

* The working torque is the torque usually reached under average working conditions. It is dependent on the highly variable ambient conditions (air pressure, hose diameter, soiling etc.).

Well-balanced device in rugged aluminum housing.

Long service life and optimum center of gravity.

Rubber-coated and ergonomically-shaped handle, 360°-rotatable additional handle, user-friendly clockwise/ counterclockwise switching and adjustable trigger.

The handle does not become cool during work.

The device is very handy and user-friendly.



360°-rotatable additional handle



Through-hole for locking pin in 1" square



Ergonomic, rubber-coated handle and 360°-rotatable air intake



The clockwise/ counterclockwise switching and the four tightening torque levels enable optimum adaptation to the respective application.

Level	Tightening torque in Nm, approx.
1	895
2	1,287
3	1,355
4	1,694



360°-rotatable air outlet on the top of the pneumatic impact wrench. The exhaust air can be expelled in the desired direction.

High-quality, high-performance pin impact mechanism in oil tank with six-vane motor.

Increased service life thanks to constant lubrication. Nearly vibration-free.

Warranty

2 Years Warranty on manufacturing and material defects. Excluded are damages caused by improper use, overloading or failure to observe the operating instructions. The current WÜRTH MASTER warranty conditions must be observed.

Accessories		
Designation	Art. No.	P. Qty.
Plug-In Nipple with R 1/2" male thread made of nickel-plated steel	0699 100 612	3
Special Oil for pneumatic tools (1 L)	0893 050 5	1
1" Power Socket Wrench Sets	0714 15...	

When used regularly, the machine should be lightly oiled via the compressed-air supply every day. The use of a mist oiler is recommended.

Available in the fleet management system ORSY®fleet.