

1-COMPONENT ASSEMBLY FOAM B3



Installation and filling foam for easy gun application

Outstanding adhesion on virtually all construction surfaces

Greater noise and heat insulation than mineral wool, cork and fibreglass

Quick-hardening

Resistant to a large number of solvents, paints and chemicals

Aging-resistant and non-rotting

Application: Safe insulation, filling and insulating of window connections, roof extensions, door frames, pipe openings, joints, wall connections, roller shutter casings, wall openings, hollow spaces etc. Sticks to concrete, brick, hard PVC, metal and wood.

Note: Does not stick to PE, PP, PTFE and silicone. Not UV-resistant.

Technical Data:

Art. No.	1892 175 0
P. Qty.	12
Content	750 ml
Chemical basis	Moisture-hardening polyurethane prepolymer
Tack free time	5 - 10 min. @ 18°C/60% RH
Cutting time	25 - 30 min. @ 18°C/60% RH
Fully cured	after 24 hours
Min./Max. processing temperature	+5°C (surface), +20°C - +25°C (can)
Yield (volume), approx.	40 - 45 l (free foamed) (750 ml)
Building material class	B3
Suitable for storage from time of manufacture	12 months

Additional articles:

PURLOGIC Xpress Foam Gun:
Art. No. 0891 1524

PURLOGIC Combipress Foam Gun:
Art. No. 0891 1526

Pump Spray Bottle:
Art. No. 0891 556

PURLOGIC PU Foam Cleaner:
Art. No. 0892 16, 0892 160