

CHAIR AND BOX ANGLE



The chair and box angles are ideal for non-static attachable Wood-wood compounds. The bilaterally countersunk Holes allow a clean Head connection.

- Both sides recessed and offset holes for optimized attachment
- For side length up to 75 mm: 2 holes
- For leg length up to 90 mm: 3 holes
- Galvanized steel sheets on both sides (St37+ A2K)
- Use in service class 1 and 2 according to EN 1995: 2013

Field of use

Non-load-bearing connections of light wood construction such as boxes, packaging, furniture or chairs or position assurance without static approach.

Manual

Suitable fasteners are ASSY 3.0 and ASSYplus countersunk screws in accordance with ETA 11/0190

Side Length x Side Length 2	Leg Width	Strength	No. of holes secondary beam nJ + main beam nH	Hole Diameter	Art.-Nr.	Qty
25 x 25 mm	14 mm	2 mm	2 + 2 Pcs	4.2 mm	0451 325	50
30 x 30 mm	14 mm	2 mm	2 + 2 Pcs	4.1 mm	0451 330	50
40 x 40 mm	15 mm	2 mm	2 + 2 Pcs	4.1 mm	0451 340	50
50 x 50 mm	15 mm	2 mm	2 + 2 Pcs	4.4 mm	0451 350	50
60 x 60 mm	18 mm	2 mm	2 + 2 Pcs	4.4 mm	0451 360	50
75 x 75 mm	17.5 mm	2 mm	2 + 2 Pcs	4.7 mm	0451 375	25
90 x 90 mm	20 mm	2 mm	3 + 3 Pcs	4.9 mm	0451 390	25
100 x 100 mm	20 mm	2.25 mm	3 + 3 Pcs	5 mm	0451 310 0	25
125 x 125 mm	23 mm	2.5 mm	3 + 3 Pcs	5.2 mm	0451 312 5	25
150 x 150 mm	25 mm	3 mm	3 + 3 Pcs	6.3 mm	0451 315 0	25