

Standard cable connector with plastic latch

For quick, problem-free and reliable bundling of cables, cable harnesses, hoses etc.

Good recycling properties

Secure grip on bundled cables

Inner toothing on tie

No additional assembly tools required

Can be attached by hand

Resistant to bases, oils, greases and motor vehicle fuels



Illustration only

Material	PA - Polyamide
Min./max. temperature resistance	-40 to 85 °C
Min./max. processing temperature	-10 to 85 °C
Silicone-free	Yes
Halogen-free	Yes

Colour	Width	Length	Min./max. bundle diameter (Bündel-Ø min./max.)	Art. no.	P. Qty.
Black	2.5 mm	100 mm	1.6-20 mm	0502 111	100/300/1000
Black	3.6 mm	140 mm	1.6-30 mm	0502 121	100/300/1000
Black	3.5 mm	200 mm	1.6-40 mm	0502 131	100/1000
Black	3.6 mm	280 mm	1.6-75 mm	0502 135 1	100/500
Black	4.8 mm	178 mm	1.6-40 mm	0502 141	100/300/1000
Black	4.5 mm	200 mm	4-68 mm	0502 141 3	100
Black	4.8 mm	280 mm	1.6-75 mm	0502 151	100/300
Black	4.8 mm	360 mm	1.6-100 mm	0502 161	100/300
Black	7.8 mm	180 mm	1.6-40 mm	0502 171	100/300
Black	7.8 mm	300 mm	5-76 mm	0502 171 3	100
Black	7.5 mm	360 mm	1.6-100 mm	0502 181	100
Black	7.8 mm	540 mm	25-150 mm	0502 190 1	100
Black	7.5 mm	750 mm	40-220 mm	0502 181 3	100
Black	12.5 mm	720 mm	48-220 mm	0502 201 1	50
Black	12.5 mm	1000 mm	48-300 mm	0502 202 2	50
Natural	2.5 mm	100 mm	1.6-20 mm	0502 11	100/1000
Natural	2.5 mm	200 mm	1-52 mm	0502 115	1000
Natural	3.6 mm	140 mm	1.6-30 mm	0502 12	100/1000
Natural	3.5 mm	200 mm	1.6-40 mm	0502 13	100/1000
Natural	3.6 mm	280 mm	1.6-75 mm	0502 135	100/500
Natural	4.8 mm	178 mm	1.6-40 mm	0502 14	100/1000
Natural	4.5 mm	200 mm	4-68 mm	0502 14 3	100
Natural	4.8 mm	280 mm	1.6-75 mm	0502 15	100
Natural	4.5 mm	360 mm	1.6-100 mm	0502 16	100
Natural	7.8 mm	180 mm	1.6-40 mm	0502 17	100

Colour	Width	Length	Min./max. bundle diameter (Bündel-Ø min./max.)	Art. no.	P. Qty.
Natural	7.5 mm	360 mm	1.6-100 mm	0502 18	100
Natural	7.8 mm	540 mm	25-150 mm	0502 19	100
Natural	7.5 mm	750 mm	40-220 mm	0502 181 31	100
Natural	12.5 mm	720 mm	48-220 mm	0502 201	50
Natural	12.5 mm	1000 mm	48-300 mm	0502 202	50

Details/Application

Control cabinet construction, installations, motor vehicle construction, motor vehicle workshops, factory workshops, elevator construction

Natural: For indoor use

Black: UV- and weather-stabilized. Carbon additives slow down the effect of UV light on the material.



Notice

- Exercise caution with strong mineral acids and/or oxidising chemicals, especially at high temperatures
- Not resistant to mineral acids and/or oxidising chemicals

Related products for	Designation	Art. no.
0502 131	Cable tie KBL 2 black With plastic latch	0502 000 131
0502 141	Cable tie KBL 2 black With plastic latch	0502 000 141
0502 151	Cable tie KBL 2 black With plastic latch	0502 000 151
0502 161	Cable tie KBL 2 black With plastic latch	0502 000 161
0502 181	Cable tie KBL 2 black With plastic latch	0502 000 181