

## S5 SRC PVC Safety Boots EN ISO 20345-2011

- Made with a special blend of PVC and nitrile rubber
- Steel toe-cap and layer
- Washable non-sweat polyester lining
- Exceptional flexibility even at low temperatures (down to -20°C)
- Black antistatic and anti-slip lug sole, resistant to hydrocarbons and mineral oils
- Completely latex-free
- Available in Yellow or Green
- Withstands impact force up to 200J and compressions up to 15 kN (S CATEGORY)

| Art. No.    | Colour | Size | Art. No.    | Colour |
|-------------|--------|------|-------------|--------|
| 535 006 137 | Yellow | 37   | 5350 05 137 | Green  |
| 535 006 138 | Yellow | 38   | 535 005 138 | Green  |
| 535 006 139 | Yellow | 39   | 535 005 139 | Green  |
| 535 006 140 | Yellow | 40   | 535 005 140 | Green  |
| 535 006 141 | Yellow | 41   | 535 005 141 | Green  |
| 535 006 142 | Yellow | 42   | 535 005 142 | Green  |
| 535 006 143 | Yellow | 43   | 535 005 143 | Green  |
| 535 006 144 | Yellow | 44   | 535 005 144 | Green  |
| 535 006 145 | Yellow | 45   | 535 005 145 | Green  |
| 535 006 146 | Yellow | 46   | 535 005 146 | Green  |
| 535 006 147 | Yellow | 47   | 535 005 147 | Green  |
| 535 006 148 | Yellow | 48   | 535 005 148 | Green  |



EN ISO 20345-2011



## PVC/BLACK OB SRA

- Cotton canvas lining
- High flexibility even at low temperatures (down to -20° C)
- Lug sole
- Color: Black
- Withstands impact force up to 200J and compressions up to 15 kN (S CATEGORY)

| Art. No.    | Colour | Size |
|-------------|--------|------|
| 535 004 138 | Black  | 38   |
| 535 004 139 |        | 39   |
| 535 004 140 |        | 40   |
| 535 004 141 |        | 41   |
| 535 004 142 |        | 42   |
| 535 004 143 |        | 43   |
| 535 004 144 |        | 44   |
| 535 004 145 |        | 45   |
| 535 004 146 |        | 46   |
| 535 004 147 |        | 47   |



EN ISO 20347

