


ALG 18 V M-CUBE charger



The ALG 18 V M-CUBE charger is specially designed for M-CUBE 18 V battery packs and offers reliable performance at an input voltage of 220 - 240 V/AC.

- For charging the Li-ion 18 V M-CUBE BASIC battery packs
- For chargers with a charging current of 8 A or more, the active cooling function of the charger ensures even faster charging of the connected battery pack

2 Years Warranty on manufacturing and material defects

Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

2 Years Warranty on batteries

The current WÜRTH MASTER warranty conditions must be observed. Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

Input voltage	230 V/AC
Min./max. output voltage	18-18 V/DC
Suitable batteries	M-CUBE 18V
Min./max. frequency	50/60 Hz
Max. output voltage	18 V/DC
Max. frequency	60 Hz
Min. frequency	50 Hz
Max. input voltage	240 V/AC
Min./max. input voltage	220-240 V/AC
Service component	Charger for machine
Output voltage	18 V/DC

Art. no.	5705 808 000	5705 180 000	5705 860 000
P. Qty.	1	1	1
Type description		ALG 18/4 BASIC	ALG 18/6 FAST
Max. charging current	8 A	4 A	6 A
Cable length	1.2 m	1.5 m	1.5 m
Length	12 cm	195 mm	195 mm
Width	22 cm	130 mm	130 mm
Height	5 cm	80 mm	80 mm
Power output	144 W		165 W
IP protection class	IP 50		
Charging time		45 min	30 min
Min./max. temperature conditions			0 to 40 °C
Max. temperature conditions	40 °C		40 °C
Min. temperature conditions		0 °C	0 °C
Product weight (per item)	899 g	760 g	1015 g
Min. output voltage	18 V	18 V/DC	18 V/DC
Plug type	C	F	F
W-CONNECT capable	No		
WEEE (taking back waste electrical and electronic equipment)	06	5	5
Nominal voltage	18 V	18 V/DC	18 V/DC