

Dot and line laser PLL 18

Self-levelling point line laser for indoor and outdoor use with highly visible red laser lines and points.

Excellent visibility of laser lines and points

- The large outlet openings in the laser create particularly long lines.
- Fine, yet clear lines

Great time-saver

Self-levelling in seconds

Simple one-button operation

All lines can be quickly and simply turned on or off with one button.

Can be used over longer distances

Can also be used for levelling over longer distances with the LRU 18 handheld receiver.

Suitable for making perpendicular lines and separating rooms

Perpendicular lines and room separations can be carried out with four laser dots, which are aligned to 90 degrees.

Level monitoring

If the self-levelling range is exceeded, the laser lines start flashing. Levelling errors are therefore eliminated.

Flexible mounting

- The laser can be attached to ceiling profiles, 1/4 and 5/8 inch tripods using the optional WM 1 universal wall mount.
- A strong magnet system supplied with the PLL-A adapter easily holds the laser on steel surfaces.

Ecological and economical

- The lithium-ion battery pack enables the device to be used while it is charging.
- Alkaline batteries can also be used (battery holder included in scope of delivery).

Laser category	2
Self-levelling range (+/-)	4 Degree
Min. working temperature	-10 °C
Max. working temperature	50 °C
Length	120 mm
Width	65 mm
Height	100 mm
IP protection class	IP 54
Battery designation	Li-lon
Range with receiver	80 m





Range without receiver	25 m
Measuring accuracy (per length)	2 mm/10m

Art. no. 5709 300 222

P. Qty.: 1

Details/Application



Contents for art. no. 5709 300 222		
Designation	Art. no.	Quantity
Target board laser	5709 300 102	1
Battery holder	5709 300 905	1
PLL-A universal bracket	5709 300 907	1
Battery for CLL 18, CLLG 18 and PLL 18	5709 300 920	1
Charging cable	5709 300 921	1
Plastic carry bag For CLL 18, CLLG 18 and PLL 18	5709 300 922	1

Related products	Art. no.
Elevator tripod made from aluminium Connection thread 5/8 inch	0714 649 303
Laser receiver Universal LRU 18	5709 300 452
WM 1 wall bracket	5709 300 908