

Rotary laser level RL5-14

Self-levelling rotary laser level for indoor and outdoor use with fibreglass-reinforced composite housing

Robust, precise laser

- Dependable device for construction sites, suitable for harsh conditions due to its robust composite housing with IP67 certification for a high level of protection against dust and water
- Extremely high level of accuracy, even in adverse weather conditions, due to compliance with ISO 17123-6
- Self-levelling in seconds for rapid alignment
- Automatic level monitoring prevents levelling errors caused by wind, soft surfaces and impacts against the tripod
- Very long range enables the accurate transfer of levels even over longer distances



Comfortable working

- Convenient operation via wireless remote control
- Uninterrupted work due to the long battery life of the Li-ion battery pack, which can be quickly recharged via the charging socket

2 Years Warranty

on issues of material and production

Laser category	2
Coverage distance	600 m
Measuring accuracy (per length)	0.75 mm/10m
Self-levelling range (+/-)	6 Degree
IP protection class	IP 67
Type of rechargeable battery/battery	Li-Ion
Number of rechargeable batteries/batteries	1 PCS
Min./max. storage temperature	-20 to 70 °C
Min. application temperature	-20 °C
Min. storage temperature	-20 °C
Max. application temperature	50 °C

Art. no. 5709 300 305

P. Qty.: 1

Details/Application

The rotary laser level is ideal for use on construction sites for transferring levels, horizontal and vertical alignment, transferring right angles and plumb points from the ground, monitoring the excavation of foundation pits, levelling batter boards, aligning

formwork, suspending ceilings and positioning partition walls.



Notice

Suitable for indoor and outdoor use.



Contents for art. no. 5709 300 305

Designation	Art. no.	Quantity
Remote control	5709 300 306	1
Li-ion battery	5709 300 902	1
Charging cable for rotary laser levels	5709 300 903	1

Related products for	Designation	Art. no.
5709 300 305	Telescopic levelling staff	0714 64 425
	Elevator tripod made from aluminium 95-269 cm	0714 649 303
	Laser receiver LR5-14	5709 300 451
	5/8" inch wall holder for rotary laser level and multi-line laser	5709 300 900