

## Cam buckle strap One piece

### For small to medium loads

- Optimum pressure and force distribution by means of a belt clamp manufactured in a die-casting process
- Also suitable for bundling loose pipes among other things



Illustration only

|           |            |
|-----------|------------|
| Standards | EN 12195-2 |
|-----------|------------|

| Art. no.                                    | 0713 92 23 | 5713 922 113        | 5713 922 114        | 5713 922 115        | 5713 922 116        | 5713 922 117        |
|---------------------------------------------|------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| P. Qty.                                     | 4          | 4                   | 1/4                 | 4                   | 4                   | 1                   |
| Design                                      |            | One-piece           | One-piece           | One-piece           | One-piece           | One-piece           |
| Width (B)                                   | 25 mm      | 25 mm               | 25 mm               | 25 mm               | 25 mm               | 35 mm               |
| Endless length                              |            | 1.2 m               | 2 m                 | 3 m                 | 5 m                 | 6 m                 |
| Length (L)                                  | 3 m        | 1.2 m               | 2 m                 | 3 m                 | 5 m                 | 6 m                 |
| Max. elongation lashing strap               |            | 5 %                 | 5 %                 | 5 %                 | 5 %                 | 5 %                 |
| Colour                                      | Red        | Red                 | Red                 | Red                 | Red                 | Red                 |
| Product certification                       |            | GS certified safety | GS certified safety | GS certified safety | GS certified safety | GS certified safety |
| Permitted tensile force LC in the strapping | 250 daN    | 250 daN             | 250 daN             | 250 daN             | 250 daN             | 700 daN             |
| Material                                    |            | PES - Polyester     | PES - Polyester     | PES - Polyester     | PES - Polyester     | PES - Polyester     |
| Min./max. temperature conditions            |            | -40 to 100 °C       | -40 to 100 °C       | -40 to 100 °C       | -40 to 100 °C       | -40 to 100 °C       |

| Art. no.                                    | 5713 922 119        |
|---------------------------------------------|---------------------|
| P. Qty.                                     | 1                   |
| Design                                      | One-piece           |
| Width (B)                                   | 35 mm               |
| Endless length                              | 6 m                 |
| Length (L)                                  | 6 m                 |
| Max. elongation lashing strap               | 5 %                 |
| Colour                                      | Black               |
| Product certification                       | GS certified safety |
| Permitted tensile force LC in the strapping | 700 daN             |
| Material                                    | PES - Polyester     |
| Min./max. temperature conditions            | -40 to 100 °C       |

### Details/Application

For commercial and private load securing in passenger vehicles, trailers, pallet trucks, delivery vans etc.



### Proof of performance

In accordance with EN 12195-2

GS-certified



### Notice

Lashing straps with coloured belt strap are not 100% colour-fast