

CUTTING DISCS FOR STEEL





The robust cutting disc with high performance values.

- Optimum cutting capacity with long service life.
- High break resistance.
- Meets the maximum safety requirements in accordance with the EN 12413 European standard.

Application area

Used to cut solid materials, pipes, profiles and metal sheets.

RED LINE

Dia. x thickn. in mm	Hole in mm	Design	max. rpm	Art.	P. Qty.
105 x 1.0	16.0		14,550	0669 201 050	100
115 x 1.0	22.23		13,300	0669 201 150	100
115 x 1.6	22.23		13,300	0669 201 151	50
125 x 1.0	22.23		12,250	0669 201 250	100
125 x 1.6	22.23		12,250	0669 201 251	50
180 x 1.8	22.23		8,500	0669 201 801	25
230 x 2.0	22.23		6,650	0669 202 302	25
100 x 2.0	16.0		15,300	0669 200 102	50
100 x 2.5	16.0		15,300	0669 201 025	50
115 x 2.5	22.23		13,300	0669 201 155	25
125 x 2.5	22.23		12,550	0669 201 255	25
180 x 2.5	22.23		8,500	0669 201 825	10/25
180 x 3.0	22.23		8,500	0669 201 803	10/25
230 x 2.5	22.23		6,650	0669 202 325	10/25
230 x 3.0	22.23		6,650	0669 202 303	10/25
250 x 3.0	19.05		6,150	0669 202 501	5/25
250 x 3.0	25.40		6,150	0669 202 503	5/25
300 x 3.0	19.05		5,100	0669 203 001	5/25
300 x 3.0	25.40		5,100	0669 203 003	5/25
350 x 2.5	25.4		4,400	0669 203 502	25
355 x 3.0 *	25.4		4,400	0669 203 553	25
355 x 3.0	25.4		4,400	0669 203 530	5/25
355 x 3.0	32.0		4,400	0669 203 550	25
355 x 3.8	25.4		4,400	0669 203 538	25
400 x 3.0	25.4		3,800	0669 204 053	25
400 x 3.0	32.0		3,800	0669 204 050	25
100 x 3.0	16.0		15,300	0669 201 003	50
115 x 2.5	22.23		13,300	0669 201 152	25
115 x 3.0	22.23		13,300	0669 201 153	25
125 x 2.5	22.23		12,250	0669 201 252	25
125 x 3.0	22.23		12,250	0669 201 253	25
180 x 3.0	22.23		8,500	0669 201 830	10/25
230 x 3.0	22.23		6,650	0669 202 330	10/25

* With single fiberglass mesh