

Grinding disc For steel and stainless steel

Synthetic resin-bonded, fibre-reinforced standard roughing wheel with very good performance values

- High breakage resistance
- Disc with medium hardness
- Free from iron, chlorine and sulphur ($\leq 0.1\%$)

Drill hole	22.23 mm
Design	Cranked
Max. circumferential speed	80 m/s
Versatility	●●○○
Service life	●●○○
Removal speed	●●○○
Removal performance	●●○○
Color Coding System	Steel  Stainless steel 



Illustration only



Diameter x thickness	Max. rotation speed	Art. no.	P. Qty.
115 x 6 mm	13300 rpm	0669 381 156	25
125 x 6 mm	12250 rpm	0669 381 256	25
180 x 6 mm	8500 rpm	0669 381 806	10
230 x 6 mm	6600 rpm	0669 382 306	10

Details/Application

- Suitable for machining steel and stainless steel
- Sanding edges and surfaces
- Dressing and smoothing
- Deburring and welding seam machining

Proof of performance

Complies with the most stringent safety requirements of European Standard EN 12413 and the OSA (the Organisation for the Safety of Abrasives)

Notice

- Storage: dry, at 20°C ambient temperature
- Work only with appropriate protective clothing
- Only use undamaged discs
- Ensure proper contact pressure
- For further information, please refer to the package insert

Related products	Art. no.
Safety goggles CEPHEUS®	0899 102 250

Related products for	Designation	Art. no.
	0669 381 156 Angle grinder EWS 7-115 Basic	5707 011 0
	0669 381 256 Angle grinder EWS 17-125-EQ POWER	5707 061 2
	Cordless angle grinder AWS 18-125 P COMPACT M-CUBE	5701 402 005
	0669 381 806 Two-hand angle grinder EWS 24-180-S	0702 445 20
0669 382 306	Safety angle grinder SWS 26-230-T	5707 090 0