

GRINDING DISC FOR STEEL AND STAINLESS STEEL

Synthetic resin-bonded, fibre-reinforced standard roughing wheel with very good performance values

- High breakage resistance
- Disc with medium hardness
- Free from iron, chlorine and sulphur ($\leq 0.1\%$)
- **Drill hole:** 22.23 mm
- **Design:** Cranked
- **Versatility (points system):** ●●○○
- **Service life (points system):** ●●○○
- **Removal speed (points system):** ●●○○
- **Removal performance (points system):** ●●○○



Complies with the most stringent safety requirements of European Standard EN 12413 and the OSA (the Organisation for the Safety of Abrasives)

Diameter x thickness	Max. rotation speed	Art. no.
115 x 6 mm	13300 rpm	0669 381 156
125 x 6 mm	12250 rpm	0669 381 256
180 x 6 mm	8500 rpm	0669 381 806
230 x 6 mm	6600 rpm	0669 382 306

GRINDING DISC FOR STEEL

The robust grinding wheel with high performance values.

Optimum grinding capacity with long service life.

High break resistance.

Meets the maximum safety requirements in accordance with the EN 12413 European standard.

- **Drill hole:** 22.23 mm
- **Design:** Cranked
- **Versatility (points system):** ●○○○
- **Service life (points system):** ●●○○
- **Removal speed (points system):** ●●○○
- **Removal performance (points system):** ●●○○



Diameter x thickness	Max. rotation speed	Art. no.
125 x 6 mm	12250 rpm	0669 661 256
230 x 6 mm	6650 rpm	0669 662 306