Pneumatic random oscillating orbital sander DTS 152C



5-mm random orbital disc (for roughening)

Robust and durable
Powerful motor and bearing with dust protection

Minimal vibrations for optimum sanding results and non-fatiguing operation
Drive features 3 balance points

Optimum adjustment to the sanding insert and paper change without disconnecting the pneumatic air
Variable speed control

For external dust extraction
Minimal dust build-up thanks to optimum extraction function with vacuum cleaners or stationary extraction systems

Ergonomic design and perfect handling
Extremely compact housing design

2-year Würth power tool guarantee on wear and tear damages.
The guarantee is subject to the current terms and conditions, which must be followed.

2 Years Warranty on manufacturing and material defects
Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

Diameter of sanding plate	150 mm
Sanding stroke	5 mm
Max. idle speed	12000 rpm
Power output	186 W
Operating pressure	6.3 bar
Air consumption	113 l/min
Weight of machine	0.71 kg
Min. hose inner diameter	9 mm
Connection thread	1/4 inch

Art. no. 0703 752 1
P. Qty.: 1

CL01_5002090207, Rev: 0.401, State: 30. 07. 2026

Details/Application

For dry sanding wood, metal surfaces, bodywork, to remove layers of paint, rust, etc. With a 5-mm random orbital disc particularly suitable for roughing

Notice

The following applies: Orbital circle = 2 x sanding stroke. The use of terms is not always standardised. Plug-in nipple not included in the scope of delivery

Related products	Art. no.
Spare parts machines, others	**0709 752 202**

Related products for	Designation	Art. no.
0703 752 1	Connection sleeve for ETS 150/hollow drill bit	**0702 400 255**
	Sanding Plate	**0586 600 013**
	Hook and loop fastener support plate for dust-free working and optimum results 150 mm Soft Multiple perforations	**0586 661 150**
	Hook and loop fastener support plate for dust-free working and optimum results 150 mm Medium Multiple perforations	**0586 662 150**
	Hook and loop fastener support plate for dust-free working and optimum results 150 mm Hard Multiple perforations	**0586 663 150**
	Plug-in nipple series 2000 14 mm 39 mm R 1/4 inch ET	**0699 100 614**
	Special oil For pneumatic tools 1 l	**0893 050 5**