


## ADAPTER FOR HIGH/LOW PRESSURE

### Renault adapter



Designation	Art. No.	P. Qty.
Adapter for vehicles with only one service port on the low-pressure side, with the connection dimensions of a high-pressure service port.	<b>0764 000 117</b>	1

## ADAPTER FOR HIGH-PRESSURE SERVICE PORT

### Extension



Designation	Art. No.	P. Qty.
The straight extension allows easier access to high-pressure service ports that are <b>difficult to access</b> due to plastic linings . <b>R134A</b>	<b>0764 000 121</b>	1
The straight extension allows easier access to high-pressure service ports that are <b>difficult to access</b> due to plastic linings . <b>R1234YF</b>	<b>1764 000 094</b>	1

## ADAPTER FOR LOW-PRESSURE SERVICE PORT

### Extension



Designation	Art. No.	P. Qty.
The straight extension allows easier access to low-pressure service ports that are <b>difficult to access</b> due to plastic linings . <b>R134A</b>	<b>0764 000 122</b>	1
The straight extension allows easier access to low-pressure service ports that are <b>difficult to access</b> due to plastic linings . <b>R1234YF</b>	<b>1764 000 686</b>	1

## ADAPTER "K"

### Connection to vehicle's air conditioner



Designation	Art. No.	P. Qty.
Used for connection between HP service port to the car air-conditioner and leak detector additive sticks.	<b>0764 000 111</b>	1

## ADAPTER "S"

### Connection to air-conditioning service unit



Designation	Art. No.	P. Qty.
Used for connection between leak detector additive stick and air-conditioning service unit.	<b>0764 000 112</b>	1

## TAMPERPROOF CLICK LOCKS

### Click Lock for R134a / R-1234yf



Designation	Art. No.	P. Qty.
A simple tamperproof seal that is placed over the existing service connections of R134a systems	<b>0764 000 450</b>	25
A simple tamperproof seal that is placed over the existing service connections of R1234yf systems	<b>1764 000 702</b>	25