

MOBILE STARTING ASSISTANCE 12V / 24V

Mobile starting assistance with 12V/24V wiring on-board power systems.

- Manual On/Off Switch.
- Reverse polarity alarm.
- Protection against voltage peaks.
- Overload protection when starting up.
- Built-in Safety fuse.
- Short-circuit-proof (protection of internal battery via high-current fuse.)
- Fully insulated, Heavy-duty angle clamps with connecting teeth in copper/brass plates.
- 100% Flexible copper cables.
- Battery charge indicated via LED lamps.
- Smart charger 3.8A





Art. No.	7721224
Nomial Voltage	12V/24V DC
Starting Current	For 12V : 850A / For 24V : 1,700A
Peak Current	For 12V : 2,500A / For 24V: 5,000A
Battery Type	AGM
Internal Battery	2 x 22 AH = 44 AH
Cable length	1.67m
Material of Housing	ABS
Weight	20 kg
Dimensions (LxWxH)	320 X 250 X 440 mm

Art. No.	Description
<i>77</i> 21238	Smart Battery Chargers
70800714	Clamps for Smart
70800715	Cigar Socket Smart
70802187	Car Charger Cable 12V
7720704	Red Curve Lamp with Fuse
7720706	Black Curve Lamp with LED
70800860	Fuse
7729322	Battery for Booster - 12V - 760A

