


MAGAZINED NAILS AND FUEL CELL

G 1.4.1



NG CS-2
Suitable for
DIGA® CS-2 POWER

Application

- High-quality all-purpose nail, 2.6 mm dia.
- Attachment of U-profiles in dry construction
- Attachments in the installation sector, dry construction etc. to concrete (\leq C40/50) as per DIN/EN 206-1 and DIN 1045 and steel and masonry made of solid brick
- A packing unit consists of 800 nails and **one** fuel cell

Nail length in mm	Nail dia. in mm	Head dia. in mm	Art. No.	P. Qty.
15	2.6	6.3	0864 950 015	800/4000
20			0864 950 020	
25			0864 950 025	
30			0864 950 030	
35			0864 950 035	
40			0864 950 040	

G 1.4.2



NG CS-2 HD
Suitable for
DIGA® CS-2 POWER

Application

- High-quality step nail for installations in plumbing and heating to a cement foundation (\leq C40/50) as per DIN/EN 206-1 and DIN 1045 and masonry made of solid brick
- A packing unit consists of 800 nails and **one** fuel cell

Nail length in mm	Nail dia. in mm	Head dia. in mm	Art. No.	P. Qty.
20	3.7	6.4	0864 950 120	800/4000
25			0864 950 125	
30			0864 950 130	
35			0864 950 135	
40			0864 950 140	

Additional articles:
Separate Fuel Cell
Art. No. 0864 900 500
Product G1.3