

# REPAIR & WATERPROOF SPRAY

## Applications

This synthetic resin spray is specially developed for waterproofing of roofs, gutters, terraces, basins, tanks, tarpaulins, blenders, pylons, metallic roofs, public works, or farming vehicles chassis. It is suitable for surfaces such as wood, metal, plastics, concrete, brick, stone, and fabrics.

## Properties

- Intended for outdoor use and ideal for temporary repairs.
- It is fluid during spraying to penetrate cracks but thixotropic (does not flow) once applied.
- Adheres without primer to most surfaces, including slightly humid ones. Dries Quickly.
- Provides immediate protection against humidity and corrosion by forming a flexible, resistant protective film.
- Can be sanded and painted after drying (prior testing is recommended).



## Technical Data

<b>Chemical Base</b>	Synthetic resin.
<b>Density</b>	0.96 g/cm
<b>Drying Time</b>	Dry to the touch in 20 minutes; fully dry in 2 to 24 hours depending on thickness temperature and humidity
<b>Coverage</b>	1 to 3 m <sup>2</sup> .
<b>Application Temperature</b>	+5°C to +40°C.
<b>Temperature Resistance</b>	-30°C to +100°C.
<b>Storage Temperature</b>	+5°C to +40°C (Avoid frost).
<b>Shelf Life</b>	60 months in original unopened packaging.

## Instructions for Use:

For optimal adhesiveness, make sure that the surfaces are clean, dust-free, free of grease and any substances that may interfere with the good adhesion of the product. Shake vigorously the spray before use. Spray from 20 - 30 cm from the surface to treat. Allow drying time between each layer. Apply several crossed layers rather than a single thick one. Bleed the nozzle after use by spraying in an upside down position to clear the nozzle and avoid clogging. Remove the excess of product while still fresh with a suitable solvent. Only a mechanical action will be able to remove the dry product.

## Precautions for use:

Outdoor use. Does not adhere to frozen surfaces. Do not apply on varnished, coated or lacquered surfaces. Allow 48 hours drying time before sanding or painting. Do not put in contact with drinking water or food. Low resistance to aggressive chemicals and hydrocarbons products. Do not apply on hot surfaces

Colour	Content:	Art. No.	Packaging
Translucent	300ml	0892 250 002	1/12



## Characteristics and Advantages

- Outdoor applications.
- Simple and quick to use, "Repair + Waterproof" is the ideal product for temporary repairs.
- Fluid during spraying, it easily penetrates cracks.
- Thixotropic, does not flow.
- Adheres without primer to most building surfaces, even those that are slightly humid.
- Fast drying, immediately effective.
- Provides protection for treated materials against humidity and corrosion.
- Forms a flexible and resistant protective film.
- Sanding and painting possible after complete drying (prior testing recommended).
- Discreet translucent shade for a clean finish.

## Product Overview

- Seals leaks, repairs, and waterproofs.
- Discreet translucent shade (Color: Translucent).