






















BLAST - AN OUTSTANDING FIELD OF VISION



Unbeatable comfort and essential modular design.

- With the "Visor" accessory the Blast model can be used as a face shield with protection guarantee.
- With or without foam (according to versions)
- Overflow chute for liquids
- All-round vision
- Fits over prescription glasses
- Ball-pivot
- Compatible with half-mask respirator
- Adjustable strap

Art.-Nr.	Versions	References	Lens Marking	Frame Marking	Coatings	
899 102294	Ventilated	BLAPSI	2-1,2  1 BT 9 CE	 EN166 3 9 BT CE	Anti-scratch/Anti-fog	
	Sealed	BLEPSI	2-1,2  1 BT 9 CE	 EN166 3 4 5 9 BT CE	Anti-scratch/Anti-fog	
	Breathable foam	BLFAPSI	2-1,2  1 BT 9 CE	 EN166 3 9 BT CE	Anti-scratch/Anti-fog	
	Ventilated Acetate	BLARSI	2-1,2  1 FN CE	 EN166 3 9 BT CE	Anti-fog (N)	
	Spare lens	FABLARSI	2-1,2  1 FN CE	-	Anti-fog (N)	
899 102994	Visor for BLAST only	BLV	 CE	 EN166 3 BT CE	-	
899 102975	Ventilated Welding shade 5	BLAWPCC5	5  1 B 9 CE	 EN166 3 9 B CE	Anti-scratch	
	Optical insert	SOSBLAST	-	-	-	

LENS MARKING

Optical class symbols:

1. Continuous work


Use symbols:

9. Molten metal and hot solids.

Mechanical strength symbols:

- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.

Others symbols:


- N.** Resistance to fogging (optional)
CE European standard  Manufacturer name

FRAME MARKING

EN166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.
4. Large dust particles > 5 microns.
5. Gas and fine dust particles < 5 microns.
9. Molten metal and hot solids.

- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.