

## BOLLE TRACKER SAFETY GOGGLES



52 g

**SUPPLIED WITH**  
Microfibre pouch



**OPTIONAL**  
Single vision Optical insert



AVAILABLE IN  
**RX**



TRACPSI



TRACPSF



TRACPSJ



TRACWPCC2



TRACWPCC3



TRACWPCC5

### TRACKER High protection

Ultra-comfortable and technical, TRACKER provides protection from all mechanical risks and also chemical risks making it unique in the safety glasses range.

- Upper protection
- Optional single vision insert
- Removable foam reinforcement
- Indirect ventilation
- Lower protection
- Removable adjustable strap
- Side ventilation

Art. No.	Lens Versions	Lens Markings	Frame marking	Coatings
<b>899 102901</b>	Clear - TRACPSI	2C-1.2 1BT KN CE	EN166 FT CE	Anti-scratch/Anti Fog
<b>899 102902</b>	Grey Smoke - TRACPSF	5-2.5 1BT KN CE	EN166 FT CE	Anti-scratch/Anti Fog
<b>899 102906</b>	Yellow - TRACPSJ	5-1.4 1BT KN CE	EN166 FT CE	Anti-scratch/Anti Fog
<b>899 102917</b>	Welding shade 1.7 - TRACWPCC2	1.7 1FT CE	EN166 FT CE	Anti-Scratch
<b>899 102903</b>	Welding shade 3 - TRACWPCC3	3 1FT CE	EN166 FT CE	Anti-Scratch
<b>899 102905</b>	Welding shade 5 - TRACWPCC5	5 1FT CE	EN166 FT CE	Anti-Scratch
<b>899 102908</b>	Spare Kit Foam & Strip	-		-
<b>899 102909</b>	Optical Spare Insert	-		-

#### LENS MARKING


##### Optical class symbols:

1. Continuous work

##### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Impact à moyenne énergie, résiste à une bille de 6 mm et de 0,86 g à 120 m/s.

##### Others symbols:

- K.** Resistance to surface damage by fine particles (optional)
- N.** Resistance to fogging (optional)
- CE European standard  Manufacturer name


#### TECHNOLOGY

##### PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching ( $1.4 \text{ cd} / \text{m}^2$ ), to the most aggressive chemicals and delays the onset of fogging for 2 minutes. In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

#### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3.** Liquid droplets or splashes.
- 4.** Large dust particles > 5 microns.
- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- CE European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

#### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.