

## LADDER IN THREE SECTIONS

It is ideal for use on different working levels: whether pulled out fully extended against the wall, or on a trestle or in a lame position. It is equipped with anti-opening straps, safety tie rod and non-slip rubber feet. It has an aluminum hook, complete with anti-slip device, for greater safety.

### Specifications:

- Adjustable base stabilizer m 1.2
- Anti-accidental opening straps
- Anti-opening/accidental closing tie rod
- Steel opening hardware
- Non-slip rubber pads
- Accidental anti-pull-out device
- Non-slip rungs mm 25x25
- Labels and use and maintenance manual
- Max capacity Kg 150
- Test certificate according to Italian (Legislative Decree 81/2008) and European UNIEN131.1.2 regulations



### Certifications



Art. No.	Number of rungs per section	Closed height mtrs	Height in the stand position mtrs.	Height in support of the wall mtrs.	Profile mm	Weight Kg	Transport Dimensions mm
962938370	3x7	2,12	2,05	3,90	60x22	13,3	2.12x0.46x0.15
962938380	3x8	2,41	2,33	4,74	60x22	14,9	2.41x0.46x0.15
962938390	3x9	2,71	2,58	5,26	60x22	16,4	2.71x0.46x0.15
962938311	3x11	3,28	3,14	6,63	73X22	21,4	3.28x0.46x0.17