

Vacuum guard for grinders



Suitable for Würth grinders EWS 24-230, EWS 24-230S and Metabo Ø 230 mm

- Reduced dust formation
- With large castors and rotating suction coupling cone
- Made of varnished steel, cutting depth can be adjusted with mounting knob
- Ability to connect to Würth vacuum cleaners using the rotating suction coupling cone: suction hose with coupling Art. 0702400249 (unscrew front part) and screw on universal coupling Art. 0702400026
- Ability to mount the anti-vibration handle Art. 0708445001 (supplied with Würth EWS 24-230/S angle grinder)
- Supplied in a cardboard box

Suitable for disc diameter	230 mm
Height	240 mm
Material	Aluminium die-cast
Suitable machines	Würth EWS 24-230, Würth EWS 24-230-S
Weight	3650 g

Art. no. 0702 445 002

P. Qty.: 1

Notice

In combination with AUTOMATIC Würth ISS 30-L, ISS 40-M, ISS 50-L vacuum cleaners

Power tools (100 to 2200 W) can be connected directly

Two-hand angle grinder EWS 24-230



2400-watt angle grinder for disks with max. 230 mm diameter.

Optimum working position

Handle can be rotated in 90° steps

Less fatigue when working

Very slim housing and vibration damping on both handles

Twist-resistant protective guard

- The hood cannot become twisted during work, offering ideal protection for the user
- Adjustable without tools, for rapid and effective work

Recoil protection

If the disc suddenly blocks, the power supply to the motor is interrupted, considerably reducing the risk of injury.

Overload indicator

To prevent motor damage, an LED comes on if the unit becomes overloaded.

On/Off switch with intelligent electronics

- Restart protection
- Overload protection
- Soft start

Optimised dust-protection concept

- Double labyrinth seals for ball bearing
- Enclosed switch
- Cool air is sucked in at the rear ventilation slots and blown out at the gear head at the front

2 Years WÜRTH MASTERPLUS Warranty for wear damage

The current WÜRTH MASTERPLUS warranty conditions must be observed.

Nominal voltage	230 V/AC
Frequency	50 Hz
Protection class	Protection class II/protective insulation
Power input	2400 W
Max. idle speed	6600 rpm
Max. cutting disc diameter	230 mm
Thread type x spindle-thread diameter	M14
Weight of machine	5.8 kg
Cable length	4 m



Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

Art. no. 0702 446 10

P. Qty.: 1

Individually boxed

Details/Application



Contents for art. no. 0702 446 10

Designation	Art. no.	Quantity
Face wrench, straight	0702 489 904	1
Clamping flange	0708 414 032	1
Handle	0708 445 001	1
Clamping nut	0708 445 031	1
Parts set	0708 445 056	1

Related products

Case for angle grinders up to Ø 230

Art. no.

0955 702 496

INDUSTRIAL WET AND DRY VACUUM CLEANER ISS 30-L AUTOMATIC



Universal vacuum cleaner suitable for construction sites with L certification and automatic filter cleaning

Dust class L certification

Guaranteed dust reduction efficiency of 99% according to EN 60335-2-69

Storage and mounting option for Würth system case

Flat container head

Accessories stored on the device and always ready to use

Integrated storage of the joint nozzle and tool sleeve with quick-action connections, flexible hose and power cord storage

Perfect for use on construction sites

Robust container with bumpers and large, sturdy metal rollers

Anti-static preparation

Thanks to the grounded connection supports and the electrically conductive accessories included in the scope of delivery, static charges are conducted away and therefore safe protection against electrostatic charging is guaranteed.

Easy to operate and control the various functions

On/off, 15 s/60 s filter cleaning and speed control switch

User-friendly work with power tools

Socket with Hall sensor for automatic power tool detection, this allows the vacuum cleaner to be controlled via a connected electric tool.

Automatic filter cleaning system

- The flat folding filter is cleaned automatically by an air blast depending on the time interval chosen (15 or 60 seconds).
- Allows long operation without interruptions
- Low noise level
- Long filter life
- Low maintenance costs

Art. No.	0701 133 0
P. Qty.	1
Air current	74 l/s
Underpressure	23 kPa
Container capacity	30 l
Max power	1380 W
Cable length	7.5 m
Hose connection diameter	35 mm

Contents for Art. No.	Designation	Art. No.	Quantity
0701 133 0	Wet/dry filter bag, fleece	0702 400 071	1
	Flat folding filter, coated	0702 400 191	1
	Suction hose, electrically conductive 3 m		1
	Joint nozzle	0702 400 390	1
	Elbow, standard	0702 400 731	1

Individually boxed

Warranty

2 Years Warranty on manufacturing and material defects. Excluded are damages caused by improper use, overloading or failure to observe the operating instructions. The current WÜRTH MASTER warranty conditions must be observed.

Application area

Ideal for carpenters, electricians, major/minor construction trades, parquet layers and tilers as well as the entire automotive sector.